Technical Information



LOBA® FloorCare



Product description

Ready to use acrylate dispersion. Protects finished and water-proof surfaces through a care layer from minor scratches and wear marks. Prevents premature wear and increases the lifetime actively. Enhances old dulled floors optically and brings new shine on floors.

Range of Use

FloorCare glossy & FloorCare matt: For finished hardwood-, cork-, linoleum-, PVC surfaces as well as unglazed stone and other water-proof surfaces. FloorCare glossy has a good resistant to alcohol and disinfectants.

FloorCare anti-slip: For hardwood floors finished with WS 2K Duo anti-slip R9.

FloorCare red brown: Colored protection layer to refresh red and brown surfaces such as magnesite floors, colored spattling compounds, red wood planks and others.

Features

FloorCare glossy & FloorCare matt

- Universally applicable care product for elastic floorings, finished hardwood floorings, finished cork floorings and other water-proof surfaces
- Good resistance against disinfectants, also suitable for doctors' offices and hospitals (only FloorCare glossy)
- Extends the lifetime of the surface
- · Covers slight wear marks

FloorCare anti-slip

- Care product especially for hardwood floors finished with WS 2K Duo anti-slip R9
- Maintains the increased slip resistance of an increased anti-slipping class R9 acc. to BGR

Technical Data

Storage and

Transportation

Article No. 10490 **Application Rate** approx.3-4 I per 100m² and application Gloss level glossy, satin, anti-slip, red brown

Package Size **Application Tool** LOBATOOL Wischwiesel

glossy 10l, 1l satin 5l, 1l

anti-slip 10l **Trockenzeiten** red brown 10l Can be carefully walked on after 1-2h **Packing** Pallet: 60 x 1I Fully stressable after 12h

Box: 4 x 5l Pallet: 128 x 5l **Thinner** Do not dilute. Product is ready to use.

Box: 12 x 1I Contents (acc. to EU-recommendations): less Pallet: 480 x 11 than 5% anionic surfactants,

+5°C to + 25°C (41°F to 77°F), preservatives. Further ingredients: storable for 24 months, no polymer dispersions, water-soluble hazardous material according to solvents.

pH-value matt: 8,5

GISCODE GE 10 (except glossy GE 20) glossy: 8,6 anti-slip: 8,8 red brown: 8,7

Technical Information



LOBA® FloorCare

Preparation:

Floor must be free from dust and soilings. Remove loose dirt and dust in advance with a vacuum cleaner, brush or mop. Afterwards damp mop floor by using LOBA® CleanFix or LOBA® Cleaner. Residues of old careproducts must be entirely removed with LOBA® CareRemover. Therefor please also regard technical informations of the respective products.

Information on Use:

Shake material well. Apply FloorCare equally on clean, dry floor with a LOBATOOL Wischwiesel (approx. 30-40 ml/m²). On larger areas a wide-headed wiper mop or another suitable applicator can be used alternatively. Put some of the material on the floor and apply in equally thick coats. Do not put any pressure on the applicator, leave the applicator on the floor during the application, do not lift. Start on one side of the room and work from wall to wall to the other side of the room in direction to the door. Do not process the floor during the drying phase, this could lead to streakings. The floor can be carefully walked on after 1-2h.

Basic Cleaning:

FloorCare all types are removable with LOBA® CareRemover, for details see technical information of the product.
FloorCare glossy, matt and red brown with a single disc machine and red/green pads. On small areas manually with a brush or scrubber.

FloorCare anti-slip with a single disc machine and medium-hard brush. On small areas manually with a brush or scrubber. When using pads anti-slip properties of the finish might get lost.

The general information on the use of LOBACARE® products and our current care instructions are part of this information and must be noticed.